

Tutorial for Sports Bra ("SPORTS – 11.5 inch fashion dolls") www.meretesyr.se

Choose a stretchy fabric that does not fray, for example cotton jersey.

You also need 6 mm (1/4 inch) wide velcro (or small sew on snaps) and a small piece of iron-on interfacing.



Licence

You are **not allowed to copy the pattern** and share with others. You are allowed to sell the finished products that you sew yourself.
www.meretesyr.se

- A. You need this pattern piece called "Sports bra".

- B. When you have cut the fabric, the piece should look like this.

Follow points 3 - 17 in the tutorial for the "Tank Top".

NB: Point 8 above can be a little tricky because the Sports bra is so small. A trick is to put a coffee filter, baking paper or something similar under the fabric when you start sewing. Tear away the paper afterwards.

- C. Cut a 11 cm (4 1/2 inch) pieces of elastic, 5 mm (3/16 inch) wide.



- D. Place a 3/16 inch (5 mm) wide elastic edge-to-edge with the lower part of the garment. Attach with pins. The elastic is a little bit shorter than the garment and it is supposed to be.



- E. Sew with an elastic stitch. In the picture a 1/8 inch (3 mm) wide and 1/8 inch (3 mm) high 3 step zigzag sewn in the middle of the elastic is shown.



This is what the wrong side should look like now.

Follow points 20 - 22 in the tutorial for "Tank Top".

- F. Finished!





Petite Barbie (left) and Barbie showing tank tops.